

PYRIDINE

H.M.S. Beagle
180 English Landing Drive
Suites 110-120
Parkville, MO 64152
816-587-9998
www.hms-beagle.com

1. Product Identification

Synonyms: Azabenzene
CAS No.: 110-86-1
Molecular Weight: 79.10
Chemical Formula: C₅H₅N
Product Codes: CHEM-243 and others.

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Pyridine	110-86-1	99 - 100%	Yes

3. Hazards Identification

Emergency Overview

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. AFFECTS CENTRAL NERVOUS SYSTEM, LIVER AND KIDNEYS. CAUSES SEVERE IRRITATION TO EYES, SKIN AND RESPIRATORY TRACT.

SAF-T-DATA^(tm) Ratings

Health Rating: 3 - Severe (Life)

Flammability Rating: 2 - Moderate

Reactivity Rating: 2 - Moderate

Contact Rating: 3 - Severe

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES; CLASS B EXTINGUISHER

Storage Color Code: Red (Flammable)

Potential Health Effects

Inhalation:

Inhalation causes severe irritation to the respiratory tract. Symptoms of overexposure include headache, dizziness, nausea, shortness of breath, coughing, insomnia, diarrhea, gastrointestinal disturbances, and back pain with urinary frequency. Liver and kidney damage may occur. May be fatal.

Ingestion:

Toxic effects parallel those of inhalation. May be fatal if swallowed.

Skin Contact:

Causes severe irritation, possibly burns, to the skin. Symptoms include redness and severe pain. Absorption through the skin may occur, resulting in toxic effects similar to inhalation. May act as a photosensitizer.

Eye Contact:

Vapors cause eye irritation. Splashes cause severe irritation, possible corneal burns and eye damage.

Chronic Exposure:

Liver and kidney damage has been reported.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin, eye or central nervous system disorders, or impaired liver, kidney, or pulmonary function may be more susceptible to the effects of this substance.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion:

If swallowed, give large quantities of water to drink and get medical attention immediately. Never give anything by mouth to an unconscious person.

Skin Contact:

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Flash point: 20C (68F) CC

Autoignition temperature: 482C (900F)

Flammable limits in air % by volume:

lel: 1.8; uel: 12.4

Flammable Liquid Contact with strong oxidizers may cause fire.

Explosion:

Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge.

Fire Extinguishing Media:

Dry chemical, foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool. Water may be ineffective.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Water may be used to flush spills away from exposures and to dilute spills to non-flammable mixtures.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. J. T. Baker SOLUSORB® solvent adsorbent is recommended for spills of this product.

7. Handling and Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Do Not attempt to clean empty containers since residue is difficult to remove. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, sparks, flame, static electricity or other sources of ignition: they may explode and cause injury or death.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

OSHA Permissible Exposure Limit (PEL) - 5 ppm (TWA).

ACGIH Threshold Limit Value (TLV) - 1 ppm (TWA), A3 - Confirmed animal carcinogen with unknown relevance to humans

NIOSH Recommended Exposure Limit (REL) - 5 ppm (Ceiling).

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a full facepiece respirator with organic vapor cartridge may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air purifying respirators do not protect workers in oxygen-deficient atmospheres. Where respirators are required, you must have a written program covering the basic requirements in the OSHA respirator standard. These include training, fit testing, medical approval, cleaning, maintenance, cartridge change schedules, etc. See 29CFR1910.134 for details.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Colorless to yellow liquid.

Odor:

Penetrating, sickening.

Solubility:

Miscible in water.

Specific Gravity:

0.98 @ 25°C/4°C

pH:

8.5

% Volatiles by volume @ 21°C (70°F):

100

Boiling Point:

115.3°C (239°F)

Melting Point:

-42°C (-44°F)

Vapor Density (Air=1):

2.72

Vapor Pressure (mm Hg):

18 @ 20°C (68°F)

Evaporation Rate (BuAc=1):

No information found.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage. Heat will contribute to instability.

Hazardous Decomposition Products:

May form cyanide fumes and oxides of carbon and nitrogen if heated to decomposition.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Heat, flame, maleic anhydride, perchromates, strong acids, strong oxidizers. Will attack some forms of plastics, rubber, and coatings.

Conditions to Avoid:

Heat, flames, ignition sources and incompatibles.

11. Toxicological Information

Toxicological Data:

Oral rat LD50: 891 mg/kg; inhalation rat LC50: 28500 mg/m³/1-hour; skin rabbit LD50: 1121 mg/kg; Irritation data: skin rabbit, open Draize, 10 mg/24H mild; eye rabbit, standard Draize, 2 mg severe. Investigated as a tumorigen and mutagen.

Ingredient	Known	Cancer Lists		IARC Category
		NTP Carcinogen	Anticipated	
Pyridine (110-86-1)	No	No	No	3

12. Ecological Information

Environmental Fate:

When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material is expected to have a half-life between 1 and 10 days. When released into water, this material may biodegrade to a moderate extent. When released into water, this material may evaporate to a moderate extent. This material is not expected to significantly bioaccumulate. When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material may be removed from the atmosphere to a moderate extent by wet deposition.

Environmental Toxicity:

This material may be toxic to aquatic life.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: PYRIDINE

Hazard Class: 3

UN/NA: UN1282

Packing Group: II

Information reported for product/size: 441LB

International (Water, I.M.O.)

Proper Shipping Name: PYRIDINE

Hazard Class: 3

UN/NA: UN1282

Packing Group: II

Information reported for product/size: 441LB

15. Regulatory Information

Ingredient	Chemical Inventory Status - Part 1			
	TSCA	EC	Japan	Australia
Pyridine (110-86-1)	Yes	Yes	Yes	Yes

Chemical Inventory Status - Part 2

Canada

Ingredient	Korea	DSL	NDSL	Phil.
Pyridine (110-86-1)	Yes	Yes	No	Yes

Federal, State & International Regulations - Part 1

SARA 302 SARA 313

Ingredient	RQ	TPQ	List	Chemical Catg.
Pyridine (110-86-1)	No	No	Yes	No

Federal, State & International Regulations - Part 2

RCRA TSCA

	CERCLA	261.33	8(d)
Pyridine (110-86-1)	1000	U196	No

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No SARA 311/312: Acute: Yes
Chronic: Yes Fire: Yes Pressure: No Reactivity: No (Pure / Liquid)

WARNING:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Australian Hazchem Code: 2WE

Poison Schedule: None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 3 Flammability: 3 Reactivity: 0

Label Hazard Warning:

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. AFFECTS CENTRAL NERVOUS SYSTEM, LIVER AND KIDNEYS. CAUSES SEVERE IRRITATION TO EYES, SKIN AND RESPIRATORY TRACT.

Label Precautions:

Keep away from heat, sparks and flame.

Keep container closed.

Use only with adequate ventilation.

Avoid breathing vapor.

Avoid contact with eyes, skin and clothing.

Wash thoroughly after handling.

Label First Aid:

If swallowed, give large amounts of water to drink. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. In all cases get medical attention immediately.

Product Use:

Laboratory Reagent and Consumer Hobby.

Revision Information:

None

Disclaimer:

H.M.S. Beagle and/or Rainbow House Alchemists, LLC, provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. NEITHER H.M.S. BEAGLE NOR RAINBOW HOUSE ALCHEMISTS, LLC MAKE NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, H.M.S. BEAGLE AND RAINBOW HOUSE ALCHEMISTS, LLC, WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by: John Farrell Kuhns
Phone Number: 816-587-9998 (U.S.A.)